

Napajanje 750W ThermalTake Smart BM2 80+ Bronze polumodularno

Šifra: 32712
Kategorija proizvoda: NAPAJANJA
Proizvođač: Thermaltake

Cena: 11.046,00 rsd.



FABU-1	
Snaga	750W
RGB Ventilator	Ne
Model	SP-750AH3CCB-B SP-750AH3CLB-B
TYPE	ATX 12V v2.4 and EPS v2.92
Maximalna snaga	750W
Boja	Black
Dimenzije (W / H / D)	150mm(W) x 86mm(H) x 160mm(D)
PFC	Active PFC
Ulazna frekvencija struje	47Hz -63Hz
Ulazni napon struje	100V-240V~ 10A max.
Dozvoljena vlaznost vazduha	20% to 90%,non-condensing 20% to 85%,non-condensing
Radni uslovi	-20 °C to +70 °C -40 °C to +55 °C
Uslovi skladistenja	5% to 95%, non-condensing 10% to 95%, non-condensing
Hladjenje	140mm Fan: 2300 R.P.M. ± 10%
Efikasnost	80 PLUS®Bronze at 115Vac input.
Predvidjen radni vek	100,000 hrs minimum
Sertifikati	cTUVus/TUV/CE/FCC/S-mark/EAC/BSMI/C-TICK/CCC
PCI-E 6+2PIN	4
PROTECTION	OVP ,OPP, OCP, OTP

P/N	PS-SPD-0750MNFABU-1
WATTS	750W
RGB FAN	No

MODEL	SP-750AH3CCB-B SP-750AH3CLB-B
TYPE	ATX 12V v2.4 and EPS v2.92
MAX. OUTPUT CAPACITY	750W
COLOR	Black
DIMENSION (W / H / D)	150mm(W) x 86mm(H) x 160mm(D)
PFC (POWER FACTOR CORRECTION)	Active PFC
POWER GOOD SIGNAL	100-500 msec
HOLD UP TIME	> 12msec at 80% of full load at 230Vac input
INPUT CURRENT	10A max. 6 - 15V
INPUT FREQUENCY RANGE	47Hz -63Hz
INPUT VOLTAGE	100V-240V~
OPERATING TEMPERATURE	0°C to +40°C +5°C to +40°C
OPERATING HUMIDITY	20% to 90%,non-condensing 20% to 85%,non-condensing
STORAGE TEMPERATURE	-20 °C to +70 °C -40 °C to +55 °C
STORAGE HUMIDITY	5% to 95%, non-condensing 10% to 95%, non-condensing
COOLING SYSTEM	140mm Fan: 2300 R.P.M. ± 10%
EFFICIENCY	Meet 80 PLUS®Bronze at 115Vac input.
MTBF	100,000 hrs minimum
SAFETY APPROVAL	cTUVus/TUV/CE/FCC/S-mark/EAC/BSMI/C-TICK/CCC
PCI-E 6+2PIN	4
PROTECTION	OVP ,OPP, OCP, OTP